


● **Outer dimensions (mm)**



TianChang sealed lead-acid rechargeable battery (VRLA battery) is leak-proof and maintenance free. The Superiority of VRLA battery is derived from its uniquely efficient oxygen recombination technology. The oxygen evolved from the positive plates diffuses through the micro porous glass fiber mat to the negative plates where it is changed back to water by recombination reaction, eliminating the need for water addition. The result is a maintenance free battery.

● **Battery Construction**

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Rubber	Copper	Fiberglass	Sulfuric acid

● **General Features**

- Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance or water adding.
- Not restricted for air transport-complies with IATA/ICAO Special Provision A67.
- UL-recognized component.
- Can be mounted in any orientation.
- Computer designed lead, calcium tin alloy grid for high power density.
- Long service life, float or cyclic applications.
- Maintenance-free operation.
- Low self discharge.

● **Application**

- Medical Equipment
- Cable Television
- Control Equipment
- UPS
- Communication Equipment
- Emergency power System
- Security System


● **Specifications**

Nominal Voltage		2V
Capacity (10 hr 25°C)		700Ah
Design Life		20 Years
Dimensions	Length	410 mm (16.14 inch)
	Width	175 mm (6.89 inch)
	Height	330 mm (12.99 inch)
	Total Height	367 mm (14.45 inch)
Approx. Weight		46 Kg
Capacity 25°C (77°F)	10 hr rate	700Ah
	3 hr rate	560Ah
	1 hr rate	455Ah
Internal Resistance (Full charged Battery at 25°C (77°F))		0.30m Ω


Capacity affected by Temperature (20hr)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-Discharge at 25°C	3 month	Remaining capacity: 91%
	6 month	Remaining capacity: 82%
	12 month	Remaining capacity: 65%
Normal operating temperature		25°C ± 3°C (77°F ± 5°F)
Operating temperature range		-15°C ~ 50°C (5 ~ 122°F)
Float charging voltage (25°C)		2.27 to 2.30V
Cyclic charging voltage (25°C)		2.42 to 2.48V
Maximum charging current		140A
Terminal material		Copper
Maximum Discharge current		4900A (5sec)

TC2-700


Charge characteristic Curve for standby use




Discharge characteristic (25°C/77°F)




Relationship between charging voltage and temperature




Self-discharge characteristic




Temperature effects on float life




Temperature effects on capacity



Life characteristics of Standby use



Cycle service life in relation to depth of discharge



F. V/Time	Constant Current Discharge Characteristics(Amperes, 25°C)								Constant Power Discharge Characteristics(Watts, 25°C)							
	5min	10min	15min	30min	1h	3h	5h	10h	5min	10min	15min	30min	1h	3h	5h	10h
1.80V	1862	1336	1008	616.0	434.0	175.0	117.6	70.0	3418.3	2404.0	1843.3	1166.7	828.3	338.3	227.5	139.3
1.75V	1960	1389	1155	686.0	441.0	182.0	122.1	70.7	3593.3	2481.8	2481.8	1306.7	844.6	355.8	239.2	140.0
1.70V	2100	1432	1231	756.0	448.0	185.5	124.6	71.4	3791.7	2559.6	2251.7	1435.0	858.7	361.7	242.7	140.7
1.60V	2450	1495	1365	840.0	455.0	189.0	124.6	72.1	4433.3	2693.9	2508.3	1610.0	870.4	367.5	245.0	141.4